

## mini acar AGD

Surge protective adapter

- + enhanced surge energy absorption
- + surge protection indicator









## Technical data: mini acar AGD

against electric shock.

recrifical data. Illin data 7100	
Maximum load	P <sub>MAX</sub> 2300W
Nominal voltage U <sub>N</sub>	230V
Nominal frequency	50Hz
Nominal load current	$\Sigma I_N = 10A \text{ MAX}$
Surge protection response time	<25ns
Maximum voltage U <sub>C</sub>	250V 50Hz
Protection level U <sub>P</sub>	≤1.3kV
Nominal discharge current i <sub>N</sub>	2kA (L/N) – 8/20μs
Maximum discharge current i <sub>MAX</sub>	10kA (L/N) – 8/20μs (type 2)
Anti-shock protection system	earthing pins connected to the protective earthing conductor
Number of socket outlets	2 two-pole socket outlets with earthing pin, 10A/250V
Housing	made of self-extinguishing plastic
Dimensions	130x56x74mm
Weight	0.12kg

addition, the **mini acar AGD** is equipped with the indicator of proper operation of the surge protection and shutters to protect

2 SOCKET OUTLETS 10A WITH EARTHING PIN AND SAFETY SHUTTERS



SURGE PROTECTION INDICATOR

The manufacturer reserves the right to change the technical parameters of the device, resulting from technological progress. ATTENTION! The technical data define the maximum values of surges against which the device protects.