

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it

RoHS₃ **Halogen Free** **Technical Datasheet** **Firestop®**
tasker® C725 PUR Double Sheathed Dante™
Extra Flex S.-U.T.P. Cat. 5e Cable – Outdoor Use



CATEGORY Long Run Transmission Data (See Data Network Catalogue)
APPLICATIONS LAN cabling, high frequency patch cord, Digital A/V over Cat. cables

- A:** Dark Blue Polyurethane (PUR) Sheath.
Flame Retardant, Halogen Free, UV, water, chemical and oil resistant.
Outer Diam. Ø 7,60 (±0,20) mm. Outdoor Use.
- B:** Soft Gray **Flame Retardant PVC** Sheath. Diam. Ø 6,40 (±0,20) mm.
- C:** O.F.C. tinned copper Braid with 85% coverage.
- D:** The four pairs are stranded together with a central synthetic filler.
- E:** Foam-skin polyethylene, Diam. Ø 1,00 mm. RJ45 plug compatible.
white/blue, white/orange, white/green, white/brown.
- F:** Stranded O.F.C. Red Copper formation 19x0,10 mm.
Section: 4x2x0,15 mm².

MARKING **tasker® C725 PUR 4x2x0,15 mm² - S.-U.T.P. - CAT.5E DOUBLE SHEATH FLEX**
ETHERNET DIGITAL SOUND FIRESTOP® – OUTDOOR USE – Made in Italy
CUSTOM PRODUCTION This product may be custom produced also in **L.S.Z.H.** polymer, **PE, PVC**,
 with or without Metallic Armor.

Cable Properties

Conductor Resistance	118 Ω/Km
Impedance	100 Ω
Max Rated Voltage	49 V
Operative Temperature	-40/+80°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS3 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver.B / 29.04.19
	X	Outdoor	Esterno		X	Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			