

DETAILS


Product Number	CA11355_LAURA-M
Family	Laura
Type	Assembly
Color	black
Diameter	21.6 x 21.6 mm
Height	13,1 mm
Style	square
Optic Material	PMMA
Holder Material	PC
Fastening	tape
Status	ready
ROHS Compliant	Yes
Date Updated	25/02/2013



OPTICAL PROPERTIES


LED	Viewing	Light	Effi-		Connector
	Angle	Beam	ciency	cd/lm	
Z5	sim: 15	Medium	-	-	-
XP-E-HEW	27 deg	Medium	85 %	2.600	-
XP-E2	28 deg	Medium	83 %	2.980	-
XT-E	28 deg	Medium	-	2.380	-
XP-E	30 deg	Medium	83 %	2.690	-
XP-G2	32 deg	Medium	83 %	2.400	-
H35C1 (LEMWA33)	33 deg	Medium	82 %	2.300	-
XP-G	34 deg	Medium	83 %	2.400	-

Relative intensity of CA11355_LAURA-M_(XP-E2)




Ledil Oy CA11355_Laura-M-Pin-XP-tape CA11355_Laura-M-Pin-XP-tape LOR=93% / LDC (Linear)


Luminaire: Ledil Oy CA11355_Laura-M-Pin-XP-tape CA11355_Laura-M-Pin-XP-tape LOR=93%
Lamps: 1 x Cree XP-E white



Luminaire: Ledil Oy CA11355_Laura-M_(XP-G2) Efficiency=83%
Lamps: 1 x Cree XP-G2 (XPGBWT-L1-0000-00FE4) 102lm @ 250mA CCT=4900K P=0.8W I=250mA




Luminaire: Ledil Oy CA11355_LAURA-M (3535_Ceramic_gen2) Efficiency=82%
Lamps: 1 x LG 3535 Ceramic gen2 (PKG5700K) 116lm @ 250mA CCT=6200K P=0.7W I=250mA




Ledil Oy CA11355_LAURA-M-BLK LOR=93% / LDC (Linear)

Luminaire: Ledil Oy CA11355_LAURA-M-BLK LOR=93%
Lamps: 1 x Cree XP-G 250mA 63.5lm Warm



Ledil Oy CA11355_Laura-M-Pin-XP-tape CA11355_Laura-M-Pin-XP-tape LOR=93% / LDC (Polar)

Luminaire: Ledil Oy CA11355_Laura-M-Pin-XP-tape CA11355_Laura-M-Pin-XP-tape LOR=93%
Lamps: 1 x Cree XP-E white




cd/klm

— C0 - C180 — C90 - C270

SIMULATED

Luminaire: Ledil Oy CA11355_Laura-M_(XP-G2) Efficiency=83%

Lamps: 1 x Cree XP-G2 (XPGBWT-L1-0000-00FE4) 102lm @ 250mA CCT=4900K P=0.8W I=250mA




cd/klm

— C0 - C180

— C90 - C270

$\eta = 84\%$

Luminaire: Ledil Oy CA11355_LAURA-M_(3535_Ceramic_gen2) Efficiency=82%
Lamps: 1 x LG 3535 Ceramic gen2 (PKG5700K) 116lm @ 250mA CCT=6200K P=0.7W I=250mA




cd/klm
— C0 - C180 — C90 - C270

Ledil Oy CA11355_LAURA-M-BLK LOR=93% / LDC (Polar)

Luminaire: Ledil Oy CA11355_LAURA-M-BLK LOR=93%

Lamps: 1 x Cree XP-G 250mA 63.5lm Warm



NOTE: The typical divergence will be changed by different color, chip size and chip position tolerance. The typical total divergence is the full angle measured where the luminous intensity is half of the peak value.

GENERAL INFORMATION

- Product series especially designed & optimized for series of LEDs.
- Special care taken to make light distribution as uniform as possible.
- Fastening to heat sink with a PU foam adhesive tape of automotive grade. Please find fastening details by clicking link: http://www.ledil.com/datasheets/DataSheet_TAPE.pdf

NOTE 1: We advise customer to ensure the suitability and sufficiency of the bond in the end product. For example, mechanical stress, vibration and holes on the surface of the circuit board weaken the strength of the tape.

NOTE 2: Assembly to the surface must be made straight, so the tape bonds constant and balanced with fastening surface. Slanted assembly might cause unbalanced bond to the surface. All surfaces where tape is applied must be clean, dry and free from grease and dirt.

If cleaning of PCB surfaces is needed, please follow strictly the cleaning instructions of your LED manufacturer - this is important as cleaning shall under no circumstances damage LEDs or other electronics components on the PCB.

Further note that optical components shall not be cleaned with any chemicals - only micro fiber cloth may be used to remove fingerprints or other traces from handling.