

tasker®

...a project further...

Features:

- Cross-linked Polyolefin
- Factor of shrinkage: 2:1
- Flame retardant
- Suitable for any use
- Highly flexible

Certifications:

- UL224 125 °C VW-1 600V file E204071
- CSA file: 1934614
- Compliant with: RoHS, Sony-SS-00259

Applications:

- Operative temperature: from -55 °C to +125 °C
- Min. temperature of shrinkage: +70 °C
- Min. temperature of shrinkage tot.: +100 °C
- Longitudinal variation: $0 \pm 10\%$ maximum

tasker®

...a project further...

<u>Code</u>	<u>Description (∅ mm)</u>	<u>Packaging</u>
GTB 1206	∅ 1,2 black+colours	m. 150 (reel)
GTB 1608	∅ 1,6 black+colours	m. 150 (reel)
GTB 2412	∅ 2,4 black+colours	m. 150 (reel)
GTB 3216	∅ 3,2 black+colours	m. 150 (reel)
GTB 4824	∅ 4,8 black+colours	m. 75 (reel)
GTB 6432	∅ 6,4 black+colours	m. 75 (reel)
GTB 9548	∅ 9,5 black+colours	m. 75 (reel)
GTB 1264	∅ 12,7 black+colours	m. 50 (reel)
GTB 1680	∅ 16,0 black+colours	m. 50 (reel)
GTB 1995	∅ 19,0 black+colours	m. 30 (reel)
GTB 2512	∅ 25,4 black+colours	m. 30 (reel)
GTB 32016	∅ 32,0 black+colours	m. 30 (reel)
GTB 3819	∅ 38,1 black+colours	m. 30 (reel)
GTB 5025	∅ 50,8 black+colours	m. 30 (reel)
GTB 7638	∅ 76,2 black+colours	m. 15 (reel)
GTB 10250	∅ 102,0 black+colours	m. 15 (reel)
GTB 12663	∅ 126,0 black	m. 15 (reel)
GTB 15076	∅ 150,0 black	m. 15 (reel)

tasker[®]

...a project further...

Standard colours	B = Blue	
	BK = Black	
	R = Red	
	W = White	
	TR = Transparent	
Colours on demand	GY = Grey	G = Green
	BR = Brown	O = Orange
	V = Violet	Y = Yellow

